

# SEALED AGM MAINTENANCE FREE

## 6 Volt Sealed AGM

Type	20 HR rate	5 HR rate	Min of Discharge @75 Amps	Min of Discharge @56 Amps	Min of Discharge @25 Amps	CCA @ 0°F -18°C	CA @ 32°F 0°C	Length	Width	Height
US AGM 2000	210	185	120	182	450	710	855	10.24" (260mm)	7.09" (180mm)	10.79" (274mm)
US AGM 250	260	226	149	228	572	745	895	11.61" (295mm)	7.09" (180mm)	11.73" (298mm)
US AGM 305	312	271	208	295	736	720	865	11.61" (295mm)	7.09" (180mm)	14.41" (366mm)
<b>US AGM L16</b>	<b>390</b>	<b>331</b>	<b>255</b>	<b>374</b>	<b>915</b>	<b>730</b>	<b>875</b>	<b>11.61" (295mm)</b>	<b>7.09" (180mm)</b>	<b>16.85" (428mm)</b>

## 12 Volt Sealed AGM

US AGM 185	234	198	125	191	518	775	930	15.24" (387mm)	7.09" (180mm)	14.49" (368mm)
US AGM 31	100	N/A	52	N/A	190	800	960	13.00" (330mm)	6.85" (174mm)	9.37" (238mm)



# US SEaled AGM

All of U.S. Battery's AGM Batteries feature the latest and most advanced paste and plate making technologies available.

**Our Premium AGM Batteries are Sealed, and Maintenance Free. They are Spill Proof, will not leak and can withstand most freezing temperatures. U.S. Battery's AGM products are also transportable by air.**